



COTTO RUSTICO

WATER/STAIN REPELLENT FOR RUSTIC TERRACOTTA – MATT FINISH

Description:

COTTO RUSTICO is a solvent based impregnator indicated for the treatment and protection of internal and external rustic terracotta surfaces such as handmade, Saltillo and highly absorbent terracotta. COTTO RUSTICO provides a complete surface protection against various staining substances such as water, oil, grease or dirt and grime caused by foot traffic. Product is breathable and will not leave surface films or coatings. UV resistant.

How to use:

Always test product first before proceeding with complete product application in order to determine final finish and products compatibility with material. Protect and cover all surroundings and metallic fixings using PVC sheeting and tape. Wear suitable PPE equipment during product use (gloves, eye protection and clothing). Product is ready for use.

On old existing surfaces: before proceeding with application remove all previous applied waxes and coatings from material using the products REMOVER or SOLV depending on state of floor.

Always apply to dry and clean surfaces. Apply COTTO RUSTICO uniformly by low pressure spray, brush or cloth to surface to be treated. Make sure all product residues are removed before allowing surface to dry completely before resuming normal use of treated area. Indicative curing time from 4 to 6 hours.

On treated materials it is possible to apply a surface finish to material to increase surface gloss. In this case, various product options are available including RIFLESSO and MIXCOTTO

Maintenance:

For routine cleaning of a internal treated surface we suggest using our product DETERCLEANER diluted in water as indicated on TDS. For periodic cleaning, please proceed to use DETERCANTIERE diluted in water for the removal of heavy dirt and grime.

Notes:

n.a.

Coverage:

1lt of product will treat from 5 to 15 m2 depending on type of material.

Packaging:

1000 ml bottles available in boxes of 10 pieces - 5000 ml containers available in boxes of 2 pieces - 10 l. and 60 l. containers available on request

Whoever before using this product, should fully read completely the product label, the technical data sheet and material safety data sheet or contact us directly for any information. We highly recommend to follow precisely all indications within supplied documentation. We highly recommend that the product is always tested first in a inconspicuous area so to determine the products compatibility and final result with the material to be treated. In all cases please maintain packaging tightly closed and always out of the reach of children. Always supply adequate ventilation when using product indoors and do not eat or drink during product use. Our technical advice, whether verbal or in writing is given in good faith without warranty and should not be considered binding towards third parties. We highly suggest that product is used always under the best professional working conditions possible. Product use and application is under the sole responsibility of the user and beyond our control. We guarantee product quality as of our production standards and supplied terms and conditions. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you.