



GIGRAF G

SOLVENT BASED, PAINT/GRAFFITI REPELLENT FOR NATURAL AND TEXTURED STONE

Description:

GIGRAF G is a solvent based, protective semi sacrificial treatment (shield) ideal for all natural stone and rough stone claddings and facades. Product penetrates deeply and adheres to material without altering or damaging the surface, protecting the material when vandalized from paint, graffiti, felt pens and other paint based materials. Products protects treated surface also from dirt deposits and is water repellent. GIGRAF G will not create any plastic effects and is UV resistant.

How to use:

Always test product first before proceeding with complete product application in order to determine final finish and products compatibility with material. Protect and cover all surroundings and metallic fixings using PVC sheeting and tape. Wear suitable PPE equipment during product use (gloves, eye protection and clothing). Product is ready for use. Do not apply where temperatures are below 10° C

On old existing surfaces: before proceeding with application remove all previous dirt and grime from surface using indicated products;

SMOG residues = NO SMOG,

GRAFFITI residues = SOLV GEL.

DIRT AND GRIME build ups = DETERMAC

Always apply to dry and clean surfaces. Apply GIGRAF G uniformly by low pressure spray or brush to surface to be treated. On highly absorbent surfaces, proceed to repeat application after 6-12 hours. Product will cure completely after 24-48 hours.

For the removal of eventual graffiti from a surface previously treated with GIGRAF G we recommend to remove all loose paint/graffiti using a pressured water jet together with the detergent DETERMAC or SOLV.

Maintenance:

n.a.

Notes:

n.a.

Coverage:

1lt of product will treat from 4 to 6 m2 on absorbent materials. On compact non absorbent surfaces product will treat from 10 – 15m2 .

Packaging:

1000 ml bottles available in boxes of 10 pieces - 5000 ml containers available in boxes of 2 pieces - 10 l. and 60 l. containers available on request

Whoever before using this product, should fully read completely the product label, the technical data sheet and material safety data sheet or contact us directly for any information. We highly recommend to follow precisely all indications within supplied documentation. We highly recommend that the product is always tested first in a inconspicuous area so to determine the products compatibility and final result with the material to be treated. In all cases please maintain packaging tightly closed and always out of the reach of children. Always supply adequate ventilation when using product indoors and do not eat or drink during product use. Our technical advice, whether verbal or in writing is given in good faith without warranty and should not be considered binding towards third parties. We highly suggest that product is used always under the best professional working conditions possible. Product use and application is under the sole responsibility of the user and beyond our control. We guarantee product quality as of our production standards and supplied terms and conditions. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you.