



IDRO G S

SOLVENT BASED, WATER REPELLENT FOR STONE, TERRACOTTA AND CONCRETE

Description:

IDRO G S will protect all stone, marble, granite and general masonry material such as brick, concrete, pavers, terracotta from rain, humidity buildup, moisture and water absorption, mildew, mould and algae, dirt and grime maintaining a constant dry surface. Treated surfaces will dry quicker after rain. Product avoids the formation of salts or efflorescence and salt spalling on treated surfaces- IDRO G S will avoid concrete or stone surfaces pitting due to potential constant humidity and dampness within the material. Product will not create any surface residue or leave plastic film effects. Long lasting, UV resistant and breathable.

How to use:

Always test product first before proceeding with complete product application in order to determine final finish and products compatibility with material. Protect and cover all surroundings and metallic fixings using PVC sheeting and tape. Wear suitable PPE equipment during product use (gloves, eye protection and clothing). Product is ready for use. Do not apply where temperatures are below 10° C.

On existing surfaces: before protecting old and existing surfaces with IDRO G S , proceed to clean and remove all previous treatments, waxes or dirt deposits from surface using our products SOLV or DETERMAC depending on residues to be removed.

Apply IDRO G S uniformly by brush, lambs-wool applicator or spray on dry and clean surfaces. Allow a curing time of 3 /4 hours before applying a second coat. We recommend allowing a full 12/24 hours curing time for complete surface protection. For applications on vertical surfaces, one coat is sufficient.

Maintenance:

-

Notes:

n.a.

Coverage:

Based on type of material and porosity, 1lt of product will cover from 4 up to 10m2.;

Packaging:

1000 ml bottles available in boxes of 10 pieces - 5000 ml containers available in boxes of 2 pieces - 10 l. and 60 l. containers available on request

Whoever before using this product, should fully read completely the product label, the technical data sheet and material safety data sheet or contact us directly for any information. We highly recommend to follow precisely all indications within supplied documentation. We highly recommend that the product is always tested first in a inconspicuous area so to determine the products compatibility and final result with the material to be treated. In all cases please maintain packaging tightly closed and always out of the reach of children. Always supply adequate ventilation when using product indoors and do not eat or drink during product use. Our technical advice, whether verbal or in writing is given in good faith without warranty and should not be considered binding towards third parties. We highly suggest that product is used always under the best professional working conditions possible. Product use and application is under the sole responsibility of the user and beyond our control. We guarantee product quality as of our production standards and supplied terms and conditions. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you.