



WET PLUS

SOLVENT BASED, PROTECTIVE WET LOOK EFFECT

Description:

WET PLUS is an enhancing, water/dirt repellent recommended for the color toning and for highlighting the materials natural colors and texture giving the stone a matt “wet look” finish. Highly recommended on absorbent natural stone surfaces such as brushed, sandblasted, bush-hammered, flamed, tumbled finishes marble, granite and natural stone. Product will protect surfaces from foot traffic, water absorption and general dirt and grime and can be applied to both internal and external surfaces. Product will not leave plastic effects and is UV resistant.

How to use:

Always test product first before proceeding with complete product application in order to determine final finish and products compatibility with material. Protect and cover all surroundings and metallic fixings using PVC sheeting and tape. Wear suitable PPE equipment during product use (gloves, eye protection and clothing). Do not apply to surfaces containing moisture or dampness. Do not apply where temperatures are below 10 °C

Apply by cloth, lambs-wool applicator or by spray on dry and clean surfaces. Apply uniformly one coat of product taking care to remove all product excess from surface. Allow to dry completely 12 - 24 hours. For applications on hard compact materials it is possible to dilute WET PLUS with SOLV using the ratio of 1:1

Maintenance:

WET PLUS is compatible with surface waxes and treatments. For daily cleaning of treated surface we recommend using our product DETERCLEANER diluted in water as indicated in TDS. For periodic or extraordinary cleaning cycles, please proceed and clean treated surface using DETERMAC diluted as indicated on TDS.

Notes:

n.a.

Coverage:

1lt of product will treat from 6 to 30 m² on absorbent materials. Coverage may vary depending on stone finish. Very absorbent materials: 6 -8m² - Medium absorbency: 10-20m² Hard compact low absorbent materials: 20 -30m²

Packaging:

1000 ml bottles available in boxes of 10 pieces - 5000 ml containers available in boxes of 2 pieces - 10 l. and 60 l. containers available on request

Whoever before using this product, should fully read completely the product label, the technical data sheet and material safety data sheet or contact us directly for any information. We highly recommend to follow precisely all indications within supplied documentation. We highly recommend that the product is always tested first in a inconspicuous area so to determine the products compatibility and final result with the material to be treated. In all cases please maintain packaging tightly closed and always out of the reach of children. Always supply adequate ventilation when using product indoors and do not eat or drink during product use. Our technical advice, whether verbal or in writing is given in good faith without warranty and should not be considered binding towards third parties. We highly suggest that product is used always under the best professional working conditions possible. Product use and application is under the sole responsibility of the user and beyond our control. We guarantee product quality as of our production standards and supplied terms and conditions. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you.